



Minimise nail & screw 'popping'

Suitable for timber & metal frames

Suitable for vertical, horizontal & overhead applications

Here comes the Stud, Adhesive

**BOSTIK ULTRAGRIP PLASTERBOARD STUD ADHESIVE
AVAILABLE JUNE, 2017**

A specially formulated non-toxic high strength acrylic stud adhesive designed to minimize nail and screw "popping" caused by timber shrinkage or frame movement.

www.bostik.com.au

Bostik
125
YEARS OF
INNOVATION

UltraGrip Stud Adhesive

A specially formulated non-toxic high strength acrylic stud adhesive designed to minimize nail and screw “popping” caused by timber shrinkage or frame movement.

SMART ADVANTAGES

- Reduces the quantity of nails and screws required to fix plasterboard
- H2 LOSP Formulated
- High bond strength
- Quick setting
- Water-based
- Non-toxic
- Non slump
- No mixing required

USES

Bostik UltraGrip is a specially formulated non-toxic high strength acrylic stud adhesive designed to minimize nail and screw “popping” caused by timber shrinkage or frame movement. Bostik UltraGrip reduces the quantities of nails and screws required to fix plasterboard, therefore reducing the fastener head stopping and finishing requirements Bostik UltraGrip can be used for:

- Fixing plasterboard to steel or timber studs and frames (in conjunction with nails and screws)
- Filling irregular gaps between plasterboard and frame
- Bonding timber to concrete or metal
- Bonding chipboard, plywood, masonite and HardieFlex™ sheeting to joints or solid floors/walls

HardieFlex™ is a trademark of James Hardie Australia

STORAGE & SHELF LIFE

Shelf life is 12 months from the date of manufacture when stored as directed (see TDS).

VOC INFORMATION

23g/litre

DIRECTIONS FOR USE

Read and understand the Safety Data Sheet before using this product. SDS can be acquired by visiting www.bostik.com.au or by scanning the relevant QR code on pack.



PRODUCT CHARACTERISTICS

Colour	Pink
Viscosity	Non-slump paste
Composition	Water based acrylic
Application Temperature	5°C - 35°C
Open time	15 minutes
Coverage	1mm thickness: 1m ² per litre
Product Codes	
850g sausage	30804611
5.2kg pail	30606231

TYPICAL PERFORMANCE DATA

Specification	Conforms to AS2753
Specific Gravity	1.46
Maximum Bond Strength	24 hours



Bostik Australia Pty Ltd
51 - 71 High Street,
Thomastown VIC 3074
Australia
www.bostik.com.au

Bostik New Zealand Pty Ltd
19 Eastern Hutt Road,
Lower Hutt 5019,
New Zealand
www.bostik.co.nz

BOSTIK HOTLINE

Smart help
1800 898 551 (AUS)
0508 222 272 (NZ)



Scan for SDS

