

# **ULTRAGRIP**

## PLASTERBOARD STUD ADHESIVE

## 9 March 2017

## YOUR SMART ADVANTAGES

- Reduces the quantity of nails and screws required to fix plasterboard
- H2 LOSP Formulated
- High bond strength
- Quick setting
- Water-based
- Non-toxic
- Non slump
- No mixing required

## USES

Bostik UltraGrip is a specially formulated non-toxic high strength acrylic stud adhesive designed to minimize nail and screw "popping" caused by timber shrinkage or frame movement. Bostik UltraGrip reduces the quantities of nails and screws required to fix plasterboard, therefore reducing the fastener head stopping and finishing requirements Bostik UltraGrip can be used for:

- Fixing plasterboard to steel or timber studs and frames (in conjunction with nails and screws)
- Filling irregular gaps between plasterboard and frame
- Bonding timber to concrete or metal
- Bonding chipboard, plywood, masonite and HardieFlex™ sheeting to joints or solid floors/ walls

PRODUCT CHARACTERISTICS	
Colour	Pink
Viscosity	Non slump paste
Composition	Water based acrylic
Application temperature	5 to 35°C
Open time	15 minutes
Coverage	1mm thickness: 1m² per litre
Product codes 850g sausage/20 per carton 5.2kg pail/4 per carton	30804611 30606231
TYPICAL PERFORMANCE DATA (approx.)	
Specification	Conforms to AS 2753
Specific gravity	1.46
	<u></u>

Maximum bond strength

24 hours

#### **DIRECTIONS FOR USE**

Read and understand the Safety Data Sheet before using this product. SDS can be acquired by visiting www.bostik.com.au or by scanning the relevant QR code on pack.

#### SURFACE PREPARATION

- 1. All surfaces must be clean, free from dirt, dust and laitance and loose material
- 2. All surfaces to be treated must be structurally sound and all previous coatings and adhesions removed prior to application of Bostik UltraGrip
- 3. All surfaces must be dry and free from moisture.
- 4. Bostik UltraGrip must be used in conjunction with nails or screws and is not single plasterboard sheet fixing system

## **APPLICATION**

## Sausage application:

- 1. Hold sausage upright and cut the top off the foil below the metal clip
- 2. Place sausage into 37cm barrel gun then screw on end cap with nozzle
- 3. With controlled gun trigger pressure, apply Bostik UltraGrip to wall studs and ceiling joists or battens in daubs 15mm to 25mm high

## Pail application:

- 1. Apply Bostik UltraGrip to walls in controlled daubs at 120mm centres and a minimum of 200mm from fixing points from the edge of the board
- 2. Ensure full contact between the sheets and Bostik UltraGrip until adhesives sets. Ceiling daubs should be 200mm and 400mm from recessed edge.
- 3. Do not nail or screw through Bostik UltraGrip. Walls should be nailed at 150mm centres, opening at 300mm centres. Ceilings should be double nailed at centre line of ceiling joists 60mm apart.
- 4. Nail edge sheets at butt joints, around openings and ceiling joist at 150mm centres. Or nail or screw the wall and ceiling sheets in accordance with board manufacturers' instructions.
- 5. Bostik UltraGrip will dry and gain full strength in 24 hours. No mixing is required, simply use directly from pail.

Bostik Australia Pty Ltd, Level 1, 6 English Street, Essendon Fields, Victoria, 3041, Australia. Tel: +61 3 9279 9333 www.bostik.com/au

Version 5 Page 1 of 2

## **BOSTIK ULTRAGRIP**

#### LIMITATIONS

- Do not use on moist or wet timber
- Do not apply to pre-painted surfaces
- Not suitable as a tile adhesive
- Internal use only
- Do not apply on unseasoned or green timber
- Use in conjunction with screws or nails to fix plasterboard.

## **CLEANING**

Remove uncured (wet) adhesive with water or Bostik Handy Wipes before adhesive cures. Cured adhesive is best removed by mechanical scraping or sanding. Use Bostik Handy Wipe towels to remove adhesive from skin

## STORAGE AND SHELF LIFE

Store in a cool dry place between 5°C and 27°C and keep out of direct sunlight. DO NOT FREEZE. Replace lid tightly when not in use. Shelf life is 12 months from the date of manufacture when stored as directed.

#### **DISPOSAL**

Empty sausages and pails may be disposed via local landfill. If spilt, absorb with clay, sand or earth. Collect and seal in properly labeled metal container. Dispose of according to local authority regulations. Do not dispose of down drains or into local waterways.

## **VOC INFORMATION**

23q/litre

## **SAFETY DIRECTIONS**

Avoid contact with skin and eyes. Wear overalls, safety shoes and impervious gloves. Avoid contact with foodstuffs and sources of heat and ignition. Wash hands after use.

FOR FIRE: If involved in a fire use water fog, foam or dry agents. Avoid breathing in products of combustion.
FOR SPILLS: Clear area of all unprotected personnel.
Slippery when spilt. Wear protective equipment. Absorb with sand or soil. Collect and seal in properly labeled drums. Refer to State/Territory Land Waste
Management Authority for disposal. Small amounts may be disposed of with household garbage.

## DO NOT RESUSE CONTAINER UNLESS THOROUGHLY DECONTAMINATED

## FIRST AID

**Swallowed:** Do not induce vomiting, give a glass of

water. Seek medical advice.

**Skin:** Remove contaminated clothing, wash skin thoroughly. If irritation occurs, seek medical advice. **Inhaled:** Remove from contaminated area. Seek medical advice.

**Eyes:** Hold open and flood with water for at least 15 minutes. Get medical advice.

Information Centre, phone 131 126 or the Emergency Response Service, phone 1800 033 111.

For emergency information contact the Poisons

HardieFlex™ is a trademark of James Hardie Australia



This datasheet is for the general help of users. It is provided in good faith. The data is current and accurate to the best of our knowledge. Differing materials, substrates, environments, site conditions, and product storage, handling and application may affect results. Users should carry out tests to decide the product's suitability for purpose. This data sheet and the properties of the product may change without notice. Users, suppliers and retailers should check that the data sheets they have are the latest. To the maximum extent permitted by law, Bostik disclaims all warranties in relation to manufacture and use of the product. Bostik is not liable for representations made by users, suppliers or retailers about the product. Bostik is not liable for any loss or damage resulting from incorrect, careless, or negligent use or storage of the product, including use of out of date product. Any liability arising from use of the product is limited to the replacement or purchase price of the product. Bostik does not exclude rights and remedies that cannot be excluded by legislation, for example under the Australian Consumer Law (ACL). Sale of the product by Bostik is subject to the Bostik Australia Proprietary Limited Conditions and Terms of Sale. For more information on Bostik, products, and conditions of use and sale visit www.bostik.com/au