

TECH DATA

Benefits

- Economical light weight construction
- Easy to install
- Available in a range of lengths and profiles to suit every requirement in regards to application and style



Cornice or cove is decorative profile made from a core of gypsum faced with heavy duty recycled paper. Paper-faced cornice enables clean-cut designs and is lightweight. It protects the plaster core and allows for easy painting. At the same time the paper facing increases the durability of the cornice profile during transportation, handling and installation.

Application

Cornice is designed to decorate and conceal the junction of walls and ceiling. It is lightweight for fast and easy installation. Cornice is available in a variety of profiles and lengths to suit application and style.

Installation

Cornice is used to complete the decoration of the building. It is fixed to walls and ceilings using cornice cements, which are setting cement adhesives available in powder form.

Cornice cements are selected depending on the length and stability of the setting time, as well as their features for practical application, such as the ability to work back the cornice cement, polish mitres and the strength of the bond.








Refer to the Knauf Plasterboard Installation guide for complete installation instructions.



Cornice is manufactured in Australia in accordance with quality systems certified as complying with AS/NZS ISO 9001:2008

TECH DATA

Product Information

CORNICE PROFILES	PROFILE NAME	WIDTH (mm)	LENGTH (mm)	WEIGHT* kg/m	CAN BE USED FOR RETROFITTING
	SkyLook	90	4200	2.04	Over existing 55mm cornice
	PacificLook	90	4200	2.3	Over existing 55mm cornice
	StepLook2	50	4200	1.64	
	StepLook3	75	4200	2.64	
	StepLook4	100	4200	2.71	
	WaveLook	75	4200	2.3	
	ClassicLook	55 75 90	from 3000 to 5400	0.78 0.92 1.35	
COMBUSTIBILITY	Classified as non-combustible according to the BCA Section C1.12				
VOLATILE ORGANIC COMPOUNDS	Less than 0.5mg/m ³ TVOC				
HAZARDS IDENTIFICATION	Not classified as hazardous according to the criteria of NOHSC Australia				

* Weights indicated are nominal

Warranty

Knauf's products are guaranteed by a 10 Year Warranty.

For details visit

knaufplasterboard.com.au

Technical Advice

AU **1300 724 505**